



1961 McGaw Ave, Irvine, CA 92614  
phone: 949.442.1601  
email: info@tempolc.com

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : C6C-55X25-UNVE5-35LG-1.IES**

**DESCRIPTION INFORMATION (From Photometric File)**

IESNA:LM-63-2002  
[TEST] 4498  
[TESTLAB] Tempo LLC  
[ISSUEDATE] 5/9/2023 2:21:48 PM  
[MANUFAC] Tempo LLC  
[LUMCAT] C6C-55X25-UNVE5-35LG-1  
[LUMINAIRE] Light gray aluminum housing with lens  
[LAMP] Sixteen (16) white LEDs (3500K) with optics  
[ELECTRICALS] 120.14 VAC, 0.0684 A, 0.9524 PF

**CHARACTERISTICS**

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	351
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	91
Total Luminaire Watts	3.85
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.70
Spacing Criterion (90-270)	0.48
Spacing Criterion (Diagonal)	0.58
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.08 ft
Luminous Width (90-270)	0.97 ft
Luminous Height	0.00 ft

**LUMINANCE DATA (cd/sq.m)**

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	7037	7822	9032
55	5230	6671	7823
65	4333	5768	5667
75	3306	4521	3357
85	1101	1728	917

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : C6C-55X25-UNVE5-35LG-1.IES**

**CANDELA TABULATION**

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
<b>0.0</b>	616.65	616.65	616.65	616.65	616.65	616.65	616.65	616.65	616.65	616.65
<b>2.5</b>	611.05	612.41	613.77	612.87	611.97	611.12	610.25	609.75	609.25	609.48
<b>5.0</b>	599.89	599.47	599.05	596.48	593.90	590.95	587.99	590.00	592.00	590.53
<b>7.5</b>	585.57	582.22	578.86	573.98	569.10	562.76	556.42	557.37	558.32	552.15
<b>10.0</b>	564.22	558.08	551.93	543.94	535.93	526.05	516.18	512.82	509.45	498.73
<b>12.5</b>	530.37	522.26	514.15	503.79	493.42	480.38	467.33	459.05	450.75	436.24
<b>15.0</b>	481.39	471.59	461.79	450.55	439.31	424.50	409.69	398.06	386.43	369.29
<b>17.5</b>	415.33	405.68	396.02	384.66	373.30	359.69	346.07	332.98	319.88	302.01
<b>20.0</b>	339.30	329.80	320.29	311.77	303.24	292.26	281.28	268.41	255.53	239.38
<b>22.5</b>	260.80	253.80	246.80	241.66	236.51	228.98	221.45	210.53	199.60	187.03
<b>25.0</b>	191.80	187.28	182.77	181.06	179.34	175.26	171.17	163.32	155.47	146.22
<b>27.5</b>	139.69	137.08	134.45	134.67	134.89	133.28	131.66	126.94	122.22	115.69
<b>30.0</b>	102.59	101.98	101.37	102.04	102.72	102.74	102.75	100.42	98.10	93.60
<b>32.5</b>	81.18	81.79	82.39	82.32	82.25	82.45	82.64	81.59	80.53	77.61
<b>35.0</b>	70.35	70.71	71.07	70.22	69.37	69.07	68.76	68.23	67.68	65.96
<b>37.5</b>	63.17	62.52	61.87	60.65	59.42	59.06	58.68	58.47	58.24	57.33
<b>40.0</b>	55.58	53.99	52.40	51.61	50.82	50.83	50.84	50.94	51.04	50.80
<b>42.5</b>	46.46	44.97	43.49	43.43	43.38	43.88	44.38	44.93	45.48	45.66
<b>45.0</b>	37.34	36.88	36.41	37.00	37.58	38.34	39.10	40.05	40.99	41.50
<b>47.5</b>	31.52	31.65	31.77	32.48	33.20	34.06	34.91	36.04	37.16	37.90
<b>50.0</b>	28.02	28.19	28.35	29.05	29.75	30.60	31.44	32.59	33.73	34.61
<b>52.5</b>	25.05	25.26	25.47	26.10	26.72	27.55	28.37	29.50	30.63	31.58
<b>55.0</b>	22.51	22.67	22.83	23.39	23.95	24.71	25.47	26.67	27.86	28.71
<b>57.5</b>	20.13	20.29	20.44	20.90	21.35	22.09	22.81	24.02	25.22	25.99
<b>60.0</b>	17.92	18.06	18.19	18.64	19.08	19.71	20.34	21.45	22.54	23.33
<b>62.5</b>	15.79	15.91	16.03	16.42	16.80	17.44	18.08	19.05	20.00	20.82
<b>65.0</b>	13.74	13.87	14.00	14.32	14.63	15.20	15.76	16.64	17.52	18.29
<b>67.5</b>	11.88	12.00	12.10	12.35	12.60	13.08	13.56	14.33	15.09	15.76
<b>70.0</b>	9.96	10.04	10.12	10.37	10.62	11.06	11.50	12.13	12.76	13.36
<b>72.5</b>	8.11	8.21	8.30	8.50	8.70	9.07	9.43	9.94	10.45	11.01
<b>75.0</b>	6.42	6.48	6.54	6.73	6.92	7.21	7.49	7.91	8.31	8.78
<b>77.5</b>	4.74	4.82	4.89	5.04	5.18	5.39	5.59	5.91	6.23	6.57
<b>80.0</b>	3.22	3.25	3.28	3.38	3.48	3.64	3.80	4.00	4.19	4.49
<b>82.5</b>	1.81	1.83	1.85	1.94	2.03	2.11	2.18	2.33	2.48	2.63
<b>85.0</b>	0.72	0.75	0.77	0.83	0.88	0.90	0.91	0.99	1.06	1.13
<b>87.5</b>	0.18	0.19	0.20	0.21	0.21	0.22	0.21	0.23	0.24	0.24
<b>90.0</b>	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**Vert. Angles**      **Horizontal Angles**

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
<b>0.0</b>	616.65	616.65	616.65	616.65	616.65	616.65	616.65	616.65	616.65
<b>2.5</b>	609.69	609.67	609.64	609.53	609.42	609.24	609.05	608.95	608.85
<b>5.0</b>	589.05	586.92	584.78	582.60	580.41	579.17	577.92	577.17	576.42
<b>7.5</b>	545.98	540.10	534.21	528.99	523.76	520.03	516.30	515.33	514.36
<b>10.0</b>	488.01	478.64	469.27	461.37	453.47	448.84	444.20	442.17	440.14
<b>12.5</b>	421.72	409.48	397.22	387.37	377.51	371.54	365.56	363.34	361.11
<b>15.0</b>	352.14	337.90	323.66	312.58	301.49	294.73	287.96	285.39	282.81
<b>17.5</b>	284.12	269.52	254.92	244.03	233.14	226.72	220.28	217.89	215.49
<b>20.0</b>	223.22	210.28	197.34	187.94	178.53	173.53	168.53	166.65	164.76
<b>22.5</b>	174.46	164.10	153.74	146.41	139.07	135.15	131.21	129.92	128.62
<b>25.0</b>	136.96	128.96	120.96	115.75	110.55	107.78	105.02	104.02	103.02
<b>27.5</b>	109.16	103.66	98.16	94.39	90.62	88.94	87.27	86.60	85.94
<b>30.0</b>	89.10	85.45	81.78	79.32	76.86	76.07	75.27	75.06	74.84

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : C6C-55X25-UNVE5-35LG-1.IES**

**CANDELA TABULATION - (Cont.)**

32.5	74.69	72.38	70.07	68.71	67.35	67.23	67.11	67.22	67.33
35.0	64.23	62.98	61.72	61.21	60.70	61.07	61.44	61.81	62.19
37.5	56.42	55.94	55.46	55.69	55.91	56.66	57.41	57.81	58.20
40.0	50.55	50.67	50.79	51.47	52.16	53.00	53.84	54.22	54.59
42.5	45.83	46.41	46.98	47.89	48.79	49.73	50.66	50.92	51.18
45.0	42.01	42.86	43.70	44.71	45.72	46.70	47.68	47.81	47.92
47.5	38.64	39.61	40.59	41.70	42.80	43.84	44.86	44.82	44.78
50.0	35.49	36.56	37.62	38.86	40.10	41.01	41.91	41.74	41.56
52.5	32.53	33.61	34.70	36.00	37.30	37.91	38.51	38.21	37.91
55.0	29.55	30.74	31.92	33.13	34.34	34.47	34.59	34.13	33.67
57.5	26.75	27.90	29.05	30.06	31.07	30.74	30.39	29.83	29.27
60.0	24.12	25.11	26.09	26.85	27.60	26.99	26.38	25.79	25.20
62.5	21.63	22.46	23.29	23.64	23.99	23.25	22.51	21.95	21.39
65.0	19.05	19.74	20.43	20.54	20.66	19.79	18.92	18.44	17.97
67.5	16.43	17.03	17.64	17.58	17.52	16.60	15.66	15.16	14.65
70.0	13.96	14.42	14.87	14.71	14.54	13.58	12.61	12.14	11.67
72.5	11.56	11.87	12.18	11.93	11.67	10.76	9.85	9.40	8.95
75.0	9.24	9.44	9.64	9.35	9.04	8.21	7.37	6.95	6.52
77.5	6.90	7.09	7.28	6.98	6.67	5.92	5.15	4.85	4.54
80.0	4.77	4.88	4.97	4.72	4.47	3.89	3.31	3.11	2.91
82.5	2.77	2.86	2.94	2.78	2.61	2.26	1.90	1.74	1.57
85.0	1.18	1.21	1.24	1.15	1.06	0.91	0.77	0.68	0.60
87.5	0.24	0.27	0.29	0.25	0.20	0.21	0.20	0.18	0.16
90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : C6C-55X25-UNVE5-35LG-1.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	154.51	N.A.	44.00
0-30	223.53	N.A.	63.60
0-40	265.63	N.A.	75.60
0-60	323.98	N.A.	92.30
0-80	349.73	N.A.	99.60
0-90	351.20	N.A.	100.00
10-90	298.04	N.A.	84.90
20-40	111.11	N.A.	31.60
20-50	143.76	N.A.	40.90
40-70	75.68	N.A.	21.50
60-80	25.74	N.A.	7.30
70-80	8.43	N.A.	2.40
80-90	1.47	N.A.	0.40
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	351.20	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	53.15
10-20	101.36
20-30	69.01
30-40	42.10
40-50	32.65
50-60	25.71
60-70	17.32
70-80	8.43
80-90	1.47
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : C6C-55X25-UNVE5-35LG-1.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70
5	89	80	73	69	87	79	73	68	77	72	68	75	71	67	74	70	67	65
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61
7	81	71	64	60	79	70	64	59	69	63	59	67	62	59	66	62	58	57
8	77	67	60	56	76	66	60	56	65	60	56	64	59	55	63	59	55	54
9	73	63	57	53	72	63	57	53	62	56	53	61	56	53	60	56	52	51
10	70	60	54	50	69	60	54	50	59	54	50	58	53	50	57	53	50	48

POLAR GRAPH



Maximum Candela = 616.65 Located At Horizontal Angle = 0, Vertical Angle = 0  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
# 2 - Vertical Plane Through Horizontal Angles (90 - 270)