



## Linear Recessed Series - Round 3



### • FEATURES:

- 3" aperture recessed fixture
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- Nearly limitless Continuous Runs



NOTE: ALL OPTIONS ITALICIZED MAY INCREASE LEAD TIMES AND/OR INCUR HIGHER COSTS - PLEASE CONSULT FACTORY WITH QUESTIONS.

FIXTURE MODEL	MOUNTING	NOMINAL LENGTH*	COLOR TEMP	LED DRIVE POWER	VOLTAGE	DRIVER
LS-LRD-3	<b>DMI</b> Dry Wall Mud-In <b>ACT15</b> 15/16" Grid Act <b>ACT9</b> 9/16" Grid Act	<b>1</b>	<b>27K</b> 2700K <b>30K</b> 3000K <b>35K</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K	<b>VLO</b> Very Low Output 405 lumens/ft. (4w/ft.)	<b>UNV</b> Universal (120-277v) <b>1V</b> 120v <b>2V</b> 227v <b>3V</b> 347v*	<b>ND</b> Non - Dimming 0-10V Dimming <b>10D</b> 10% DIM <b>1D</b> 1% DIM LUTRON <b>LDE1</b> Lutron EcoSystem 1% "Soft on" (Digital) <b>LDE5</b> Lutron EcoSystem 5% 5-Series (Digital) DAL <b>DALI</b> Digital Addressable Lighting Interface
		<b>2</b>		<b>LO</b> Low Output 610 lumens/ft. (6w/ft.)		
		<b>3</b>		<b>SO</b> Standard Output 795 lumens/ft. (8w/ft.)		
		<b>4</b>		<b>HO</b> High Output 1,000 lumens/ft. (10w/ft.)		
		<b>5</b>		<b>VHO</b> Very High Output 1,160 lumens/ft. (12w/ft.)		
		<b>6</b>		<b>CPO</b> Custom Power Output Consult factory		
		<b>7</b>				
		<b>8</b>				
		<b>CR__</b>				
		*Dimensions are for reference only. Contact factory for more specific information or shop drawings. **Odd lengths may incur slightly higher per foot pricing.				
				*Not Applicable with CSD option.		*Not all dimming options are available with 347v.

HOUSING FINISH	OPTIONS/CUSTOMIZATION*
<b>SW</b> Satin White (Powder Coat)	<b>EMB7</b> 7 Watt battery back-up** (Approximately 600 lumens)
<b>CF</b> Custom Finish* (Consult Factory)	<b>EMB12</b> 12 Watt battery back-up** (Approximately 1,000 lumens)
	<b>CCP</b> lumens
	<b>CD</b> 90+ CRI LED BOARDS
	<b>CR</b> Corners/patterns*
	<b>WSN</b> Custom Driver*
	<b>WSE</b> Customization Requested*
	<b>WSW</b>
	<b>WSL</b> Night Air Enlighted Wavelinx Lutron Vive
	NOTE: Customization may incur higher costs and/or increased lead times. *Consult the factory for all custom options or custom concept requests. **The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE INTEGRAL).
*RAL and color match are available.	

### GENERAL NOTES:

All fixtures are UL listed for dry and damp locations. Fixtures with International (E) option designation are CE and ROHS compliant. INTEGRAL DRIVER for all options. Please contact the factory with any specification questions.



### FIXTURE ORIENTATION

Direct (CSD) for downlight applications  
Indirect (CSI) for up light applications  
Rotational (CSR) for adjustable applications: 360 degree rotational capacity with locking mechanism.

## Linear Recessed Series - Round 3

### PRODUCT SPECIFICATION

- FIXTURE DELIVERED LIGHT POTENTIAL: 108 LUMENS/WATT\*
- UNIFORM LIGHT DISTRIBUTION
- 90+ CRI LED DIODE OPTIONS
- EXCEPTIONAL BINNING - LESS THAN 2 STEP MACADAMS ELIPSE
- MINIMUM 70% INITIAL LUMEN OUTPUT AT 70,000 HOURS
- STANDARD 0-10V DIMMING TO %10
- LUTRON, ELDOLED, DALI, AND OTHER DIMMING OPTIONS
- 5 YEAR SYSTEM WAXRRANTY

\*Actual fixture efficacy will be dependent on specification. Higher lumens per watt are achieved with lower drive powers. Please contact the factory with questions or for more information.

### LUMEN OUTPUT\*

#### LUMEN OUTPUT (PER FOOT)

DRIVER OUTPUT	WATTAGE	LUMENS
VERY LOW (VLO)	4	390
LOW (LO)	6	590
STANDARD (SO)	8	775
HIGH (HO)	10	970
VERY HIGH (VHO)	12	1,130

#### PER 4' FIXTURE (TOTAL DELIVERED LUMENS)

DRIVER OUTPUT	WATTAGE	LUMENS
VERY LOW (VLO)	16	1,560
LOW (LO)	24	2,360
STANDARD (SO)	32	3,100
HIGH (HO)	40	3,880
VERY HIGH (VHO)	48	4,520



### ZONAL LUMEN SUMMARY

ZONE	LUMEN	%LAMP	%FIXTURE
0 - 30	945	21.9%	30.4%
0 - 40	1,509	34.9%	48.6%
0 - 60	2,528	58.5%	81.4%
0 - 90	3,105	71.9%	100%

### FIXTURE PROPERTIES (AS TESTED)

- 4' nominal length fixture
- Standard Output (SO)
- Total system energy consumption: 64 Watt
- 99 Lumens/Watt
- 4000K 80 CRI LED

### LUMINOUS INTENSITY DISTRIBUTION



### GENERAL NOTES:

All fixtures are UL listed for dry and damp locations. Fixtures with International (E) option designation are CE and ROHS compliant. INTEGRAL DRIVER for all options. Please contact the factory with any specification questions.



### FIXTURE ORIENTATION

Direct (CSD) for downlight applications  
 Indirect (CSI) for up light applications  
 Rotational (CSR) for adjustable applications: 360 degree rotational capacity with locking mechanism.